

<b>Tag Number</b> <b>BFP</b>		Parts to include SS tag with tag name	
<b>Specification</b>			
<b>Fluid:</b> Water <b>Contaminants:</b> <b>Temperature:</b> 33 to 180 F                      (or 0.6 - 82 C) <b>Pressure:</b> 150 psi Maximum              (or 10 Bar) <b>pH:</b> Neutral		<b>Process Conditions</b>	
Backflow Preventor - Reduced Pressure Principle, Conbraco 40-200 series or equivalent to include ball valves for all sizes.		<b>Typical Selection</b>	
Per the P&ID's or the equipment list.		<b>Pipe Size</b>	
Bronze                              1/4 inch to 2 inch range Epoxy coated Ductile Iron      2.5 inch to 10 inch range		<b>Body Material</b>	
FNPT X FNPT                      1/4 inch to 2 inch range Flanged, ANSI 150 lb B16.5      2.5 inch to 10 inch range		<b>End Connection</b>	
Stainless Steel		<b>Springs</b>	
Buna N and Nylon		<b>Diaphragms</b>	
Silicone Rubber                      1/4 inch to 2 inch range Bronze                                  2.5 inch to 10 inch range		<b>Seats</b>	
<b>Notes:</b> <div></div>		<div> <div>Rev</div> <div>Date</div> <div>0</div> <div>7-Apr-10</div> </div>	
<div>By</div> <div>JLP</div>		<div>Reviewed</div> <div></div>	
<div>Approved</div> <div></div>		<div>Dwg Number</div> <div>STD-46.1 BFP</div>	
		<div>THIS DRAWING AND ALL INFORMATION THEREON IS THE PROPERTY OF SMI AND IS CONFIDENTIAL. THIS DRAWING AND INCLUDED INFORMATION MUST NOT BE MADE PUBLIC OR COPIED WITHOUT SMI PERMISSION. IT IS SUBJECT TO RETURN ON DEMAND.</div>	
		<div>VALVE TEMPLATE v1 29Jan08.xls</div>	
		<div>Page</div> <div>1 of 1</div>	



**Specialty**  
**MINERALS**

Process Engineering  
1 Highland Ave. Bethlehem, PA  
18017