

Tag Number	GV2	Valve to includes SS tag with tag name	
Valve Specification			
Acidic Water, Direct Contact water		Service	
Globe valve, 150 lb ANSI class Flanged, Stainless Steel		Typical Selection	
Globe		Type Valve	
0 - 150 psig or 0 - 10 bar		Pressure Range	
-40F to 190F or -40C to 90C		Temperature Range	
1-4		pH Range	
Stainless Steel 316		Body Material	
Flanged ANSI 150 lb class 2 inch to 8 inch range		End Connection	
Handwheel		Valve Operator	
		Body Construction	
Trim - 316 SS Packing -Teflon (PFTE)		Trim Material	
Disc-Plug Seat integral		Trim Construction	
Notes:		Rev	Date
		1	17-Apr-10
By	Reviewed	Approved	Dwg Number
JLP			STD-46.1 GV2
		THIS DRAWING AND ALL INFORMATION THEREON IS THE PROPERTY OF SMI AND IS CONFIDENTIAL.THIS DRAWING AND INCLUDED INFORMATION MUST NOT BE MADE PUBLIC OR COPIED WITHOUT SMI PERMISSION. IT IS SUBJECT TO RETURN ON DEMAND.	
		VALVE TEMPLATE v1 29Jan08.xls	
		Page	
		1 of 1	



Specialty
MINERALS

Process Engineering
1 Highland Ave.
Bethlehem, PA 18017