

Tag Number ST5		Parts to include SS tag with tag name	
Specification			
Fluid: Chemical Liquid Services Contaminants: Various Temperature: -20 to 150 F (or -29C to 65 C) Pressure: 200 psig maximum (or 0-14 Bar) pH:		Process Conditions	
Wye Strainer, Cast Stainless Steel, Flanged, Mueller 781-SS or Equivalent		Typical Selection	
Per the P&ID's or the equipment list.		Pipe Size	
Cast Stainless Steel, ASTM A351 CF8M		Body Material	
Flanged, ANSI 150 lb B16.5 Available Range 1/2 inch to 8 inch		End Connection	
.035" or 20 Mesh, 304 Stainless Steel		Screen basket	
Notes:		Rev 1	Date 1-Mar-17
By MRB		Reviewed	
Approved		Dwg Number STD-46.1 ST5	
		THIS DRAWING AND ALL INFORMATION THEREON IS THE PROPERTY OF SMI AND IS CONFIDENTIAL. THIS DRAWING AND INCLUDED INFORMATION MUST NOT BE MADE PUBLIC OR COPIED WITHOUT SMI PERMISSION. IT IS SUBJECT TO RETURN ON DEMAND.	
		VALVE TEMPLATE v1 29Jan08.xls	
		Page 1 of 1	



Process Engineering
 1 Highland Ave. Bethlehem, PA
 18017