

Tag Number		ST2		Parts to include SS tag with tag name	
Specification					
Fluid: Water or Steam Contaminants: Various Temperature: -20 to 150 F (or -29C to 65 C) Pressure: 200 psig maximum (or 0-14 Bar) pH: Neutral				Process Conditions	
Wye Strainer - Mueller 351M or equivalent				Typical Selection	
304SS				Screen MOC	
Bronze ASTM B62				Body Material	
FNPT X FNPT				End Connection	
20 mesh unless specified differently on P&ID				Mesh	
NPT without plug.				Blowoff Outlet	
Notes:				THIS DRAWING AND ALL INFORMATION THEREON IS THE PROPERTY OF SMI AND IS CONFIDENTIAL. THIS DRAWING AND INCLUDED INFORMATION MUST NOT BE MADE PUBLIC OR COPIED WITHOUT SMI PERMISSION. IT IS SUBJECT TO RETURN ON DEMAND.	
				Rev 0 Date 3-Apr-10	
By MRB		Reviewed		Page 1 of 1 VALVE TEMPLATE v1 29Jan08.xls	
		Approved			
		Dwg Number STD-46.1 ST2			



**Specialty**  
MINERALS

Process Engineering  
1 Highland Ave. Bethlehem, PA  
18017