

Tag Number	BF2	Valve to includes SS tag with tag name	
Valve Specification			
Water, PCC (CaCO3),Slake (Ca(OH)2 or Flue gas.		Service	
Butterfly valve, manual Deltech series 52 or equivalent		Typical Selection	
Butterfly valve		Type Valve	
0 - 150 psig or 0 - 10 bar		Pressure Range	
-40F to 190F or -40C to 90C		Temperature Range	
3 to 13		pH Range	
Cast Carbon Steel ASTM A216 (WCB)		Body Material	
<u>Lug</u> For ANSI 150 lb class Flanges range 2-20 inch		End Connection	
Lever with locking handle 2-12 inch, Gear operated 14-20 inch		Valve Operator	
Disc-316 Stainless Steel Shaft - Stainless Steel		Body Construction	
Trim - 316 SS Seat EPDM		Trim Material	
		Trim Construction	
Notes:		Rev 1	Date 17-Apr-10
By JLP		Reviewed	Approved
Dwg Number STD-46.1 BF2		Page 1 of 1	



Specialty
MINERALS

Process Engineering
1 Highland Ave.
Bethlehem, PA 18017

THIS DRAWING AND ALL INFORMATION THEREON IS THE PROPERTY OF SMI
AND IS CONFIDENTIAL.THIS DRAWING AND INCLUDED INFORMATION MUST
NOT BE MADE PUBLIC OR COPIED WITHOUT SMI PERMISSION. IT IS
SUBJECT TO RETURN ON DEMAND.
VALVE TEMPLATE v1 29Jan08.xls