

Tag Number PI2		Parts to include SS tag with tag name									
Specification											
Fluid: Slake Slurry Ca(OH) ₂ , PCC Slurry CaCO ₃ , Water, Air Contaminants: Temperature: < 170 F (or 77 C) Pressure: 150 psig maximum (or 10 Bar) pH: 7-13		Process Conditions									
Pressure Gage, Liquid Filled, Phenolice Turret Case, Poly propylene thread Ring, USG Model 1981L or equivalent		Typical Selection									
1/2 inch MNPT 4 1/2 inch Diameter, Petra Turret Case Surface Stem		End Connection Face Dial Mounting									
316 Stainless Steel 316 Stainless Steel		Bourdon Tube Connection Material									
Referece PID's or Equipment list. Most Common, 0-160psi, 0-60 psi, 0-100 psi, -30 to 15 psi.		Range									
Notes:		<table border="1"> <tr> <td><u>Rev</u></td> <td><u>Date</u></td> </tr> <tr> <td>0</td> <td>8-Apr-10</td> </tr> </table>		<u>Rev</u>	<u>Date</u>	0	8-Apr-10				
<u>Rev</u>	<u>Date</u>										
0	8-Apr-10										
<table border="1"> <tr> <td><u>By</u></td> <td><u>Reviewed</u></td> <td><u>Approved</u></td> <td><u>Dwg Number</u></td> </tr> <tr> <td>JLP</td> <td></td> <td></td> <td>STD-46.1 PI2</td> </tr> </table>		<u>By</u>	<u>Reviewed</u>	<u>Approved</u>	<u>Dwg Number</u>	JLP			STD-46.1 PI2	THIS DRAWING AND ALL INFORMATION THEREON IS THE PROPERTY OF SMI AND IS CONFIDENTIAL. THIS DRAWING AND INCLUDED INFORMATION MUST NOT BE MADE PUBLIC OR COPIED WITHOUT SMI PERMISSION. IT IS SUBJECT TO RETURN ON DEMAND. VALVE TEMPLATE v1 29Jan08.xls	
<u>By</u>	<u>Reviewed</u>	<u>Approved</u>	<u>Dwg Number</u>								
JLP			STD-46.1 PI2								
		<table border="1"> <tr> <td>Page</td> </tr> <tr> <td>1 of 1</td> </tr> </table>		Page	1 of 1						
Page											
1 of 1											



Specialty
MINERALS

Process Engineering
1 Highland Ave. Bethlehem, PA
18017