

Tag Number		FI-SLAKER		Parts to include SS tag with tag name	
Specification					
Fluid: Water Contaminants: Temperature: 200 F (or 93 C max) Pressure: 125 psig (or 8.6 Bar) pH: Neutral				Process Conditions	
Rotary Site Flow Indicator, McMaster Carr 4200K42, or equivalent				Typical Selection	
3/8 inch FNPT				Pipe Size End Connection	
Bronze				Body Material	
Glass, 2 13/16 inch long x 2 1/8 inch wide				Window	
Stainless Steel				Shaft and Pin	
Buna N				Gasket	
Notes:				THIS DRAWING AND ALL INFORMATION THEREON IS THE PROPERTY OF SMI AND IS CONFIDENTIAL. THIS DRAWING AND INCLUDED INFORMATION MUST NOT BE MADE PUBLIC OR COPIED WITHOUT SMI PERMISSION. IT IS SUBJECT TO RETURN ON DEMAND.	
				Rev 0 Date 9-Apr-10	
By JLP		Reviewed		Approved Dwg Number STD-46.1 FI-SLAKER	
				VALVE TEMPLATE v1 29Jan08.xls	
				Page 1 of 1	



Specialty
MINERALS

Process Engineering
1 Highland Ave. Bethlehem, PA
18017